



Architectural Systems

Edition 2.3





Contents

Door Systems:

Harbourview Multi-folding Door 4
Cityview Sliding/Stacking Patio Door 6
Cityview Sliding Apartment Door 8

Window Systems:

Cityview Sliding Window 10
Cityview Awning Window/High Performance Awning Window 12
Cityview Double Hung Window 14
Cityview Louvre Window 16

Commercial Framing 18





Above picture courtesy of Dyna-Fix Commercial

The "Cityview™" & "Harbour™view" range of window and door systems & commercial framing are the ideal choice for modern architectural requirements, meeting current design trends as well as performance specifications.

The systems are ideally suited for high end residential and commercial developments and apartments.

The systems can be incorporated in a variety of louvre, awning, double hung, sliding and multi-fold configurations by using a common framing system, which allows for a wide range of design options.

The entire "Cityview™" & "Harbour™view" range can accept single or double glazing options, this allows the flexibility to meet all budgets, plus allows the design to achieve today's stringent energy and noise requirements.







Maximise your living space and seamlessly join indoor and outdoor activities by using a "harbour™ view" multi-fold door or window system.

The "Harbour™ View" system incorporates quality "BRIO - WEATHERFOLD 4s" hardware components and features a polypropylene track insert which reduces noise and extends the life of the rollers, ensuring years of trouble free, smooth operation.



Harbour[™]view Multi-folding Door System


Design features

- Max. panel height: 3200mm(Conditions Apply)
- Max. weight per door panel: 100kg
- Max. glass thickness: 24mm

Options

- "Harbour™view" multi-fold's provide choice, left or right opening directions, inward or outward swinging panels, dozens of configuration options available including a single access door when using a non-even configuration.
- A screening option is available by incorporating the BRIO 612 Retractable Insect screen.
- Bottom Sills can also be made less obtrusive by recessing into floors.

Door configurations (Inward or Outward swinging panels)















Designed to suit modern architectural requirements, when you're looking for quality then the Cityview Patio Door is it!

This Sliding Door system offers a vast amount of configurations to suit just about any opening!

Simple and cost effective like the sliding door, stacker doors are ideal if you want a wide opening. They open to two thirds of their width allowing indoor living areas to be connected to patios, sundecks, courtyards and gardens.


Fly door / security door tracks are already incorporated into the framing design so no addon tracks are required for screening.




Sliding / Stacking Patio Door

Design features

- Max. door panel size: 2700mm(H) x 1350mm(W)
- Max. weight per door panel: 120kg
- Max. glass thickness: 20mm













Designed with strength and high performance in mind.

This sliding door series is either used in high rise building applications or just when you require the ultimate in high performance.

Its structural design allows for extra large door panels and glass thicknesses of up to 24mm can be achieved.

Add-on tracks are available for screening purposes.

Available in a range of durable powder coat colours.

A choice of architectural locks are available to suit your individual taste.


The Cityview door requires minimal maintenance and is very quiet to operate.





Sliding Apartment Door


Design features


- Maximum size per door panel = 2700mm (H) x 1500mm (W).
- Maximum weight per door panel = 160kg.
- Maximum glass thickness = 24mm



























Framing a view beautifully without distraction using Cityview Sliding Windows. The unobtrusive design presents clean and sleek, minimalist result with a sense of openness and freedom.


Sliding Window


Design features


- Side-lights, high-lights and low-lights possible
- Accepts glass thickness from 6mm to 20mm
- Max. panel size: 1800mm(H) x 1200mm(W)
- Max. panel weight: 100kg

Options

- · Range of heavy duty stiles for different strength requirements
- Internal fly screen
- Heavy duty rollers
- Vent lock to restrict opening for additional security and safety above first floor applications.















Hinged from the top and opening outward, "Cityview" awning windows are designed to provide continuous ventilation whilst partly opened during inclement weather. They can be positioned in a variety of places being able to stack vertically, combine horizontally or coupled with fixed panels or other windows and doors.

The design using compression seals around the perimeter, these seals provide superior weatherproofing, saving energy, lowering noise and creating all year round comfort.

Locking options are camlock or chain-winder, the chain-winder allows easy operation without interfering with insect / fly or security screens.



Awning Window


Design features

- Max. size per sash: 1200mm(H) x 800mm(W)
- Max. weight per sash: 35kg (Depending on stay option)
- Max. glass thickness: 24mm

Options

100mm restricted opening for security and above first floor applications.

Supported configurations




High Performance Awning Window


Design features

- Max. size per sash: 1500mm(H) x 1200mm(W)
- Max. weight per sash: 130kg
- Max. glass thickness: 30mm

Options

100mm restricted opening for security and above first floor applications.













For traditional character or a modern contemporary look, the "Cityview" double hung window makes it a popular style choice in windows today.

Providing the ultimate in ventilation control, allowing you to circulate air and control humid conditions in an instant.

Featuring a concealed balance operating system, the aluminium double hung window will provide you with years of trouble free operation.

Also built- in as a design feature is our unique finger grip groove for easy operation of both top and bottom sash.

A key lockable cam lock provides security as a standard feature.



Double Hung Window


Design features


- Max. size per sash: 1000mm(W) x 800mm(W).
- Max. weight per sash: 18kg.
- Max. glass thickness: 18mm


Options


100mm restricted opening for security and above first floor applications





























The "Cityview" Louvre window is a modern alternative that provides exceptional controlled ventilation. Enjoy natural light with convenient weather control and the freedom to let in the amount of fresh air you prefer. It is a proven performer, developed to withstand the harshest environments and achieving performance ratings that meet the stringent requirements of Australian standards for windows.

A choice of glass, timber or powder coated aluminium blades are available. The louvre blades are secured by unique UV stabilised injection-moulded clip that provides a weather tight seal and is corrosion-free.

"Cityview" louvres can be fitted with an integrated insect screens that does not interfere with the operation of the louvre blades.

Options include a barrier bar system, key locks and motorization is available.



Louvre Window

Design features

- Max. panel size: 2400mm(W) x 800mm(W).
- Max. blade thickness: 14mm
- Blade spans up to 900mm wide

Options


- Glass, Timber or Aluminium blade option.
- Left or right hand side controls available.
- Manual control pole option for out of reach applications.
- · Concealed Motorised remote control option.
- 102mm or 152mm blades











Retirement Village



School



Toyota Dealership







School Auditorium

Commercial Framing

Offers a wide range of framing options to meet your requirements, these include widths between 76mm and 150mm, front pocket or centre pocket and single glazed and double glazed options.

The entire range has undergone stringent australian standards testing at an independent nata approved laboratry.



Shopping Centre







Sydney head office

8 Tyrone Place, Erskine Park NSW 2759

Tel: (02) 8887 2888 Fax: (02) 9834 3244

Email:sales@darleyaluminium.com.au

Melbourne

10 Bridge Road, Keysborough VIC 3173 Tel: (03) 9238 3888 Fax: (03) 9768 7288

Email:salesvic@darleyaluminium.com.au

Brisbane

29 Access Avenue, Yatala QLD 4207

Tel: (07) 3287 1888 Fax: (07) 3287 2088

Email:salesqld@darleyaluminium.com.au

Perth

36 Armstrong Road, Hope Valley WA 6165

Tel: (08) 9437 2999 Fax: (08) 9437 1024

Email:saleswa@darleyaluminium.com.au









Contact your fabricator: